

Switch-disconnector, DMM, 125 A, 4 pole, with blue knob, cylinder lock, in CI-K5 enclosure



Part no. **DMM-125/4/I5/C-B**
172861

Product name	Eaton DMM Switch-disconnector
Part no.	DMM-125/4/I5/C-B
EAN	4015081694419
Product Length/Depth	280 millimetre
Product height	160 millimetre
Product width	200 millimetre
Product weight	2.465 kilogram
Certifications	IEC/EN 60947 IEC/EN 60204 KEMA CE RoHS VDE 0660 EAC IEC/EN 60947-3 Lloyds
Product Tradename	DMM
Product Type	Switch-disconnector
Product Sub Type	None
Globally Marketable	Yes
	in CI-K5 enclosure Rated Short-time Withstand Current (I _{cw}) for a time of 1 second
Features	Version as main switch Version as maintenance-/service switch
Fitted with:	Blue knob
Functions	Interlockable
Locking mechanism	Cylinder lock
Number of poles	Four-pole
Accessories	Auxiliary contact fitted by user.
Degree of protection	NEMA 12
Degree of protection (front side)	IP65
Lifespan, mechanical	10,000 Operations
Mounting method	Surface mounting
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (U _{imp})	6000 V
Safety parameter (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
Suitable for	Ground mounting
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	40 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	80 °C
Terminal capacity	6 - 70 mm ² , flexible with ferrules to DIN 46228
Stripping length (main cable)	21 mm
Tightening torque	7 Nm, Screw terminals

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)			1000 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)			528 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)			336 A
Rated insulation voltage (Ui)			1000 V
Rated operational current (Ie) at AC-21, 400 V, 415 V			125 A
Rated operational current (Ie) at AC-21, 500 V			125 A
Rated operational current (Ie) at AC-21, 690 V			125 A
Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V			125 A
Rated operational current (Ie) at AC-22, 500 V			125 A
Rated operational current (Ie) at AC-22, 690 V			125 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V			125 A
Rated operational current (Ie) at AC-23A, 500 V			66 A
Rated operational current (Ie) at AC-23A, 690 V			42 A
Rated operational power at AC-23A, 400 V, 50 Hz			59 kW
Rated operational power at AC-23A, 500 V, 50 Hz			45 kW
Rated operational power at AC-23A, 690 V, 50 Hz			37 kW
Rated operational power at AC-3, 380/400 V, 50 Hz			0 kW
Rated operational voltage (Ue) at AC - min			690 V
Rated operational voltage (Ue) at AC - max			690 V
Rated uninterrupted current (Iu)			125 A
Uninterrupted current			Rated uninterrupted current Iu is specified for max. cross-section.
Breaking current			13.7 kA
Let-through energy			Max. 134 kA²s
Rated conditional short-circuit current (Iq)			50 kA 30 kA at 415 V
Rated short-time withstand current (Icw)			2.5 kA 2,5 kA, Contacts, 1 second
Short-circuit protection rating			125, Fuse, Contacts
Number of auxiliary contacts (change-over contacts)			0
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0
Actuator color			Other
Actuator type			Short thumb-grip
Equipment heat dissipation, current-dependent Pvid			4.9 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			4.5 W
Rated operational current for specified heat dissipation (In)			125 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			UV resistance only in connection with protective shield.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])			
Version as main switch			Yes
Version as maintenance-/service switch			Yes
Version as safety switch			No
Version as emergency stop installation			No
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage Ue AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current Iu		A	125
Rated permanent current at AC-23, 400 V		A	66
Rated permanent current at AC-21, 400 V		A	125
Rated operation power at AC-3, 400 V		kW	0
Rated short-time withstand current Icw		kA	2.5
Rated operation power at AC-23, 400 V		kW	59
Switching power at 400 V		kW	0
Conditioned rated short-circuit current Iq		kA	50
Number of poles			4
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Complete device in housing
Suitable for floor mounting			Yes
Suitable for front mounting 4-hole			No
Suitable for front mounting centre			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Colour control element			Other
Type of control element			Short thumb-grip
Interlockable			Yes
Type of electrical connection of main circuit			Screw connection
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			12